

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number  
**WO 2005/096218 A1**

(51) International Patent Classification<sup>7</sup>: **G06K 9/32**,  
7/10, G06T 1/00

(21) International Application Number:  
PCT/AU2005/000445

(22) International Filing Date: 30 March 2005 (30.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2004901730 31 March 2004 (31.03.2004) AU  
2004901731 31 March 2004 (31.03.2004) AU  
2004901732 31 March 2004 (31.03.2004) AU

(71) Applicant (for all designated States except US): **CANON KABUSHIKI KAISHA** [JP/JP]; 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LARKIN, Kieran,**


**Gerard** [AU/AU]; 22 Mitchell Street, Putney, NSW 2112 (AU). **FLETCHER, Peter, Alleine** [AU/AU]; 56 Lilyfield Road, Rozelle, NSW 2039 (AU). **HARDY, Stephen, James** [AU/AU]; 67 Wyomee Avenue, West Pymble, NSW 2073 (AU).

(74) Agent: **SPRUSON & FERGUSON**; GPO Box 3898, Sydney, NSW 2001 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: IMAGING SYSTEM PERFORMANCE MEASUREMENT



(57) Abstract: A method (1000) of measuring performance parameters of an imaging device (120, 160) is disclosed. The method (1000) maintains a test pattern image (1005), the test pattern image (1005) comprising alignment features and image analysis features. A test chart (110, 170) containing a representation of the test pattern image is next imaged using the imaging device (120, 160) to form a second image (1010). The test pattern image (1005) and the second image (1010) are then registered using region based matching (1035) operating on the alignment features. Finally, the performance parameters are measured by analysing (1060) the image analysis features.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*